

Master Safety Data Sheet

Section 1 - Identification of the Substance/Mixture and of the Company/Undertaking

Covers all Accurate Aerosol Universal Blend aerosol colors

Accurate Aerosols, LLC
P.O. Box 201156
Cartersville, GA 30120
770-467-7553

Emergency Phone (Day) M-F 8a-5p EST: 770-467-7553
Emergency Phone (Night) All other Hours:
Health - Poison Control Center: 315-476-4766
Spills - Chemtel: 1-800-255-3924

Product Use: Paint
Not recommended for: No Information Available.

Section 2 - Hazards Identification

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see supplemental first aid instruction on this label)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water

P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use water spray, carbon dioxide (CO ₂), dry powder or dry chemical foam for extinction.
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with all local, jurisdictional, national and international regulations

Signal Word: Danger



Section 3 - Composition Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Acetone	67-64-1	10.00% - 30.00%
Xylene	1330-20-7	10.00% - 30.00%
Propane	74-98-6	3.00% - 7.00%
N-Butyl Acetate	123-86-4	3.00% - 7.00%
Butane	106-97-8	1.00% - 5.00%
EthylBenzene	100-41-4	1.00% - 5.00%
Methyl N-Amyl Ketone	110-43-0	1.00% - 5.00%
Ethyl 3-ethoxypropionate	763-69-9	1.00% - 5.00%
Solvent naphtha, petroleum, light aromatic (Aromatic #100)	64742-95-6	1.00% - 5.00%
Solvent, naphtha, petroleum, heavy aromatic (Aromatic #150)	64742-94-5	1.00% - 2.00%
1,2,4 Trimethylbenzene	95-63-6	1.00% - 2.00%
Mineral Spirits	8052-41-3	0.10% - 1.00%

Section 4 - First Aid Measures

4.1 Description of First Aid Measures

General Advice - Show this safety data sheet to the doctor in attendance.

Inhalation - Move to fresh air. If symptoms persist, call a physician.

Eye Contact - Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately.

Skin Contact - Wash off immediately with soap and plenty of water. Take off contaminated clothing. Get medical attention if irritation persists.

Ingestion - Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately if symptoms occur.

Protection of First-aiders - Remove all sources of ignition. Use personal protective equipment.

Section 5 - Firefighting Measures

Flash Point: -28 C (-18 F)

LEL: 1.00

UEL: 13.00

5.1 Extinguishing Media

Suitable Extinguishing Media - Carbon Dioxide (CO₂). Dry powder. Dry chemical foam. Water spray.

Unsuitable Extinguishing Media - Do not use a solid water stream as it may scatter and spread fire.

5.2 Special Hazards Arising from the Substance or Mixture - Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustible Products - No additional information available.

5.3 Advice for Firefighters - As in any fire, wear self-contained breathing apparatus and full protective gear.

Protective Equipment - Do not enter a fire area without proper protective equipment, including respiratory protection. Wear a self containing breathing apparatus.

Section 6 - Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures - ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

6.2 Environmental Precautions - Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and Materials for Containment and Cleaning Up - A vapor suppressing foam may be used to reduce vapors. Dike far ahead of liquid spill for later disposal.

Dam up. Soak up with inert absorbant materials (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use clean non-sparking tools to collect absorbed material. Keep in suitable, closed containers for disposal.

Section 7 - Handling and Storage

7.1 Precautions for Safe Handling - Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Hygiene Measures - When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

7.2 Conditions for Safe Storage, Including Any Incompatibilities - Keep containers tightly closed in a dry, cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

7.3 Regulatory Requirements - No additional information.

Section 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m ³ TWA
Xylene 1330-20-7	100 ppm TWA; 435 mg/m ³ TWA	150 ppm STEL 100 ppm TWA	Not Established
Propane 74-98-6	1000 ppm TWA; 1800 mg/m ³ TWA	See Appendix F: Minimal Oxygen Content	NIOSH: 1000 ppm TWA; 1800 mg/m ³ TWA

N-Butyl Acetate 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
Butane 106-97-8	Not Established	1000 ppm STEL	NIOSH: 800 ppm TWA; 1900 mg/m3 TWA
EthylBenzene 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
Methyl N-Amyl Ketone 110-43-0	100 ppm TWA; 465 mg/m3 TWA	50 ppm TWA	NIOSH: 100 ppm TWA; 465 mg/m3 TWA
Ethyl 3-ethoxypropionate 763-69-9	Not Established	Not Established	Not Established
Solvent naphtha, petroleum, light aromatic (Aromatic #100) 64742-95-6	Not Established	Not Established	Not Established
Solvent, naphtha, petroleum, heavy aromatic (Aromatic #150) 64742-94-5	Not Established	Not Established	Not Established
1,2,4 Trimethylbenzene 95-63-6	Not Established	Not Established	NIOSH: 25 ppm TWA; 125 mg/m3 TWA
Mineral Spirits 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)

8.1 Engineering Controls - Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion proof ventilation equipment.

Ventilation - Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapor. Avoid discharge to the environment.

Administration Controls - No information available.

8.2 Exposure Controls - Avoid all unnecessary exposure. Gloves. Protective Goggles. For certain operations, additional Personal Protective Equipment (PPE) may be required.

Hand Protection - Wear protective gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Impervious gloves (neoprene) should be worn to protect against skin contact. A combination of barrier cream, applied before exposure and gloves is recommended.

Eye Protection - Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.

Skin and Body Protection - Wear suitable protective clothing. Chemical resistant safety shoes. Protective apron.

Respiratory Protection - Wear appropriate mask. A NIOSH/MSHA approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits. In applications where aerosols or vapors are emitted, a full face organic vapor cartridge respirator with a particulate pre-filter should be worn. In confined areas and in emergency situations, use a self-contained breathing apparatus or other air supplied full face respirator.

Contaminated Gear: Launder mildly contamination clothing. Dispose of moderate/heavily contaminated clothing, including shoes.

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Vapor Pressure: 293.9 mmHg Weight Per Gallon 7.02 Boiling range: 56°C Viscosity - 2Z 30-35 SEC #2 ZAHN Lbs VOC/Gallon Less Water 4.04	Odor Aromatic Vapor Density: 2.4 Freezing point: N/A Flash Point -18 F,-28 C Grams VOC/Liter Less Water 484.5
--	--

Section 10 - Stability and Reactivity

10.1 Reactivity - No data available.

10.2 Chemical Stability - Product is stable under recommended conditions.
 STABLE

10.3 Incompatible Materials - Strong oxidizing agents. Strong bases. Strong acids.

10.4 Conditions to Avoid - Heat, flames and sparks.
 No additional information available

10.5 Possibility of Hazardous Reactions - None under normal processing.

10.6 Hazardous Decomposition Products - Carbon oxides. Hydrogen Chloride. Hydrogen Fluoride.
 No additional information available
 Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity
 Inhalation Toxicity LC50: 78mg/L

Component Toxicity

67-64-1	Acetone Dermal LD50: 1,700 mg/kg (Rabbit)
100-41-4	EthylBenzene Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)

11.1 Information on Toxicological Effects -

Target Organ Effects - Central nervous system (CNS). Respiratory system.

Acute Toxicity
 Inhalation - May cause irritation of respiratory tract.
 Eye Contact - Irritating to eyes. Causes serious eye irritation.
 Skin Contact - Causes skin irritation.
 Ingestion - Ingestion may cause irritation to mucous membranes.

100-41-4 Ethylbenzene
 If the coating contains ethylbenzene. Ethylbenzene is classified by IARC as possibly carcinogenic to humans (group 2B) based on inadequate evidence in humans & sufficient evidence in lab animals. Lifetime inhalation exposure to high concentrations of ethylbenzene in mice & rats results in increases in certain types of cancer, such as liver & lung tumors in mice & kidney tumors in rats. These effects were not seen when the animals were exposed to lower concentrations. There is no evidence ethylbenzene causes cancer in humans.

1333-86-4 Carbon Black
 If the coating contains carbon black. Carbon black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal testing data. However there is insufficient evidence in humans for its carcinogenicity.

13463-67-7 Titanium Dioxide

If the coating contains titanium dioxide. Titanium dioxide is classified by IARC as possibly carcinogenic to humans (group 2B). Titanium dioxide is suspected of causing cancer by inhalation, which is not a viable route of entry as all titanium dioxide is dispersed into a liquid mixture in coatings.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
106-97-8	Butane	1 to 5%	Butane: EU REACH: Present (C) (containing >=0.1% Butadiene)
8052-41-3	Mineral Spirits	.1 to 1.0%	Mineral Spirits: EU REACH: Present (P)
64742-95-6	Solvent naphtha, petroleum, light aromatic (Aromatic #100)	1 to 5%	Solvent naphtha, petroleum, light aromatic (Aromatic #100): EU REACH: Present (P)

Section 12 - Ecological Information

General Notes - Avoid release to the environment.

Component Ecotoxicity

Acetone	96 Hr LC50 Oncorhynchus mykiss: 4.74 - 6.33 mL/L; 96 Hr LC50 Pimephales promelas: 6210 - 8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L 48 Hr EC50 Daphnia magna: 10294 - 17704 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 - 12700 mg/L
Xylene	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L
N-Butyl Acetate	96 Hr LC50 Lepomis macrochirus: 100 mg/L [static]; 96 Hr LC50 Pimephales promelas: 17 - 19 mg/L [flow-through] 72 Hr EC50 Desmodemus subspicatus: 674.7 mg/L
EthylBenzene	96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]
Methyl N-Amyl Ketone	96 Hr LC50 Pimephales promelas: 126 - 137 mg/L [flow-through]
Ethyl 3-ethoxypropionate	96 Hr LC50 Pimephales promelas: 62 mg/L [static] 48 Hr EC50 Daphnia magna: 970 mg/L
Solvent naphtha, petroleum, light aromatic (Aromatic #100)	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L 48 Hr EC50 Daphnia magna: 6.14 mg/L

Solvent, naphtha, petroleum,
heavy aromatic (Aromatic #150)

96 Hr LC50 Pimephales promelas: 19 mg/L [static]; 96 Hr LC50 Oncorhynchus
mykiss: 2.34 mg/L; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static]; 96 Hr
LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Pimephales
promelas: 41 mg/L
48 Hr EC50 Daphnia magna: 0.95 mg/L

1,2,4 Trimethylbenzene

96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
48 Hr EC50 Daphnia magna: 6.14 mg/L

Section 13 - Disposal Considerations

13.1 Waste Treatment Methods

Waste from Residues/Unused Products - Dispose of in accordance with local regulations.

Contaminated Packaging - Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14 - Transportation Information

Disclaimer: Any given paint product can be shipped in different size containers, ranging from a pint can to bulk tanks. The shipping regulations in the United States vary depending on container size. The Basic Description given below are for shipments in fully regulated non-bulk containers, where the UN ID number, Proper Shipping Name, (technical names, if any), Packing Groups & Hazard Class (subsidiary risks, if any) are given. This section does not cover packaging exceptions, such as smaller quantities that can be shipped in combination packages i.e. Limited Quantity or Consumer Commodity with or without basic descriptions or shipping papers. Also not covered are exceptions given for products that do not sustain combustion and are excepted from regulations under certain modes of transportation. Nor for products containing Reportable Quantities (RQ's) of hazardous substances when shipped in bulk, but not reportable when shipped in non-bulk packaging. All subsequent shipping of this product must be done by properly trained and certified employees under the specific competent authority's regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	AEROSOLS	1950	N/A	2.1
IATA	AEROSOLS, FLAMMABLE	1950	N/A	2.1
IMDG	AEROSOLS	1950	N/A	2

Section 15 - Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture - DSL

100-41-4 EthylBenzene 1 to 5 %
123-86-4 N-Butyl Acetate 3 to 7 %
1330-20-7 Xylene 10 to 30 %
67-64-1 Acetone 10 to 30 %

In compliance with DSL Inventory requirements for commercial purposes.

Massachusetts Right to Know

8052-41-3 Mineral Spirits 0.1 to 1.0 %
95-63-6 1,2,4 Trimethylbenzene 1 to 2 %
110-43-0 Methyl N-Amyl Ketone 1 to 5 %
100-41-4 EthylBenzene 1 to 5 %
106-97-8 Butane 1 to 5 %
123-86-4 N-Butyl Acetate 3 to 7 %
74-98-6 Propane 3 to 7 %
1330-20-7 Xylene 10 to 30 %
67-64-1 Acetone 10 to 30 %

In compliance with Massachusetts Right to Know Inventory requirements for commercial purposes.

New Jersey Right to Know

8052-41-3 Mineral Spirits 0.1 to 1.0 %
95-63-6 1,2,4 Trimethylbenzene 1 to 2 %
110-43-0 Methyl N-Amyl Ketone 1 to 5 %

- 100-41-4 EthylBenzene 1 to 5 %
- 106-97-8 Butane 1 to 5 %
- 123-86-4 N-Butyl Acetate 3 to 7 %
- 74-98-6 Propane 3 to 7 %
- 1330-20-7 Xylene 10 to 30 %
- 67-64-1 Acetone 10 to 30 %

In compliance with New Jersey Right to Know Inventory requirements for commercial purposes.

Pennsylvania Right to Know

- 8052-41-3 Mineral Spirits 0.1 to 1.0 %
- 95-63-6 1,2,4 Trimethylbenzene 1 to 2 %
- 110-43-0 Methyl N-Amyl Ketone 1 to 5 %
- 100-41-4 EthylBenzene 1 to 5 %
- 106-97-8 Butane 1 to 5 %
- 123-86-4 N-Butyl Acetate 3 to 7 %
- 74-98-6 Propane 3 to 7 %
- 1330-20-7 Xylene 10 to 30 %
- 67-64-1 Acetone 10 to 30 %

In compliance with Pennsylvania Right to Know Inventory requirements for commercial purposes.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the state of California as carcinogenic or a reproductive toxin:

- 100-41-4 EthylBenzene 1 to 5 %

The following items are reportable under SARA 312.

- 100-41-4 EthylBenzene
- 123-86-4 N-Butyl Acetate
- 1330-20-7 Xylene
- 67-64-1 Acetone

The following items are reportable under SARA 313.

- 95-63-6 1,2,4 Trimethylbenzene
- 100-41-4 EthylBenzene
- 1330-20-7 Xylene

TSCA

- 8052-41-3 Mineral Spirits 0.1 to 1.0 %
- 95-63-6 1,2,4 Trimethylbenzene 1 to 2 %
- 64742-94-5 Solvent, naphtha, petroleum, heavy aromatic (Aromatic #150) 1 to 2 %
- 64742-95-6 Solvent naphtha, petroleum, light aromatic (Aromatic #100) 1 to 5 %
- 763-69-9 Ethyl 3-ethoxypropionate 1 to 5 %
- 110-43-0 Methyl N-Amyl Ketone 1 to 5 %
- 100-41-4 EthylBenzene 1 to 5 %
- 106-97-8 Butane 1 to 5 %
- 123-86-4 N-Butyl Acetate 3 to 7 %
- 74-98-6 Propane 3 to 7 %
- 1330-20-7 Xylene 10 to 30 %
- 67-64-1 Acetone 10 to 30 %

In compliance with TSCA Inventory requirements for commercial purposes.

WHMIS

- 8052-41-3 Mineral Spirits 0.1 to 1.0 %
- 95-63-6 1,2,4 Trimethylbenzene 1 to 2 %
- 64742-95-6 Solvent naphtha, petroleum, light aromatic (Aromatic #100) 1 to 5 %
- 763-69-9 Ethyl 3-ethoxypropionate 1 to 5 %
- 110-43-0 Methyl N-Amyl Ketone 1 to 5 %
- 100-41-4 EthylBenzene 1 to 5 %
- 106-97-8 Butane 1 to 5 %
- 123-86-4 N-Butyl Acetate 3 to 7 %
- 74-98-6 Propane 3 to 7 %
- 1330-20-7 Xylene 10 to 30 %

67-64-1 Acetone 10 to 30 %

In compliance with WHMIS Inventory requirements for commercial purposes.

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

- None

Section 16 - Other Information

User's Responsibility - The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required as an individual operation to instruct employees and develop work practice procedures for a safe work environment. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. To the best of our knowledge, the information contained herein is accurate. However, Accurate Aeorsols, LLC assumes no liability whatsoever for the accuracy, reliability or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. Since conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by use of this material. All materials may present unknown health and safety hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Date revised: 2016-02-02

Reviewer Revision 1

Date Prepared: 2/2/2016